



PTC 20N

Professional 20x Zoom NDI Camera



Professional Video Collaboration Camera

Get crystal clear images with this professional PTZ camera. Compatible with all leading cloud VC applications, the PTC 20N has a variety of interfaces that make it perfectly suited for auditoria, seminar halls, and conference rooms. The 20x zoom delivers sharp images that show every small detail. Bundled software allows you to manage the camera easily.

Capture sharper videos

Enhance Your Video Collaboration Experience



Powerful zoom

The powerful sensor with 20x zoom deliver sharp images that makes sure that every detail is captured

Easy live streaming

Live stream directly from the camera without any hassles















amera	
Image Sensor	1/2.8" CMOS, 2.14MP
Focal Length	f=4.7 - 94.0mm
Iris	F1.6 - F3.5
Optical Zoom	20X
Digital Zoom	12X
FOV	60°
Focus System	Auto, Manual, PTZ Trigger, One Push Trigger
Exposure Control	Auto, Manual, Shutter Priority, Iris Priority
Shutter Speed	1/1 ~ 1/10,000s
Gain	Auto/Manual
White Balance	Auto, Manual, Indoor, Outdoor
Wide Dynamic	Yes
BLC	Yes
DNR	2D/3D
SN Ratio	>50dB
TZ	
Pan Angle/ Speed	-170° ~ +170°, 0.1° ~ 120°/S
Tilt Angle/ Speed	-30° ~ +90°, 0.1° ~ 80°/S
Presets	256
OSD	Yes
Image Flip	Yes
	163
ideo Output	4000-50/50/20/25 4000/50/50 700-50/50
Video Format	1080p60/50/30/25, 1080i60/50, 720p60/50
etwork	
Max Image Size	1920×1080@60fps
Image Compression	H.264/H.265
Audio Compression	AAC
Protocols	ONVIF, RTSP, RTMP, HTTP, TCP, UDP
Dual Stream	Support
	Support
terface	Зарроге
terface Video Output	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet
Video Output	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN
Video Output Audio	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal)
Video Output Audio Network Interface	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN
Video Output Audio Network Interface Control Interface NDI	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT
Video Output Audio Network Interface Control Interface	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT
Video Output Audio Network Interface Control Interface NDI eneral	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT Supported
Video Output Audio Network Interface Control Interface NDI eneral Protocols Power	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT Supported VISCA (support daisy chain), PELCO-P, PELCO-D
Video Output Audio Network Interface Control Interface NDI eneral Protocols	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT Supported VISCA (support daisy chain), PELCO-P, PELCO-D DC12V
Video Output Audio Network Interface Control Interface NDI eneral Protocols Power Power Consumption	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT Supported VISCA (support daisy chain), PELCO-P, PELCO-D DC12V <15W
Video Output Audio Network Interface Control Interface NDI eneral Protocols Power Power Consumption Operating Temperature	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT Supported VISCA (support daisy chain), PELCO-P, PELCO-D DC12V <15W 0°C ~ +40°C
Video Output Audio Network Interface Control Interface NDI eneral Protocols Power Power Consumption Operating Temperature Storage Temperature Dimensions L×W×H	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT Supported VISCA (support daisy chain), PELCO-P, PELCO-D DC12V <15W 0°C ~ +40°C -20°C ~ +60°C 243mm×145mm×163mm
Video Output Audio Network Interface Control Interface NDI eneral Protocols Power Power Consumption Operating Temperature Storage Temperature	1×HDMI, 1×3G-SDI, 1×USB2.0, 1×Ethernet 1×LINE IN 10/100/1000M RJ45, PoE (optinal) 1×RS-485, 1×RS-232 IN, 1×RS-232 OUT Supported VISCA (support daisy chain), PELCO-P, PELCO-D DC12V <15W 0°C ~ +40°C -20°C ~ +60°C

^{*}OPTIONAL ACCESSORIES - WALL MOUNT, CEILING MOUNT, PTZ JOYSTICK CONTROLLER, CABLES

+91 452 4392222

■ sales@atnetindia.net

www.atnetindia.net