



A&T[™]



PTC PRO

Professional PTZ Camera


Applications: Conference Room | Board Room | Training Hall | Auditorium



1080P60



20X / 30X
Optical Zoom



USB, HDMI, IP



NDI HX / SRT



PTC PRO

SPECIFICATION



Camera	PTC Pro-20X	PTC Pro-30X
Image Sensor	1/2.8" CMOS, 2.14 MP	
Iris	F1.6 ~ F3.5	F1.8~4.8
Focal Length	4.7mm ~ 94mm	f=5.2~155.8mm
HFov	59.5°	59°
Optical zoom	20X	30X
Digital Zoom	16x	
Focusing System	Auto, Manual, PTZ Trigger, One Push Trigger	
Shutter Speed	1/50 ~ 1/10,000s	
AGC	Auto, Manual	
BLC	Support	
White Balance	Auto, One Push, Manual, ATW, Static Color Temperature	
Wide Dynamic	Support	
Exposure	Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority	
SNR	≥50dB	
Interface		
HDMI	1080P60/P50/P30/P25,720P60/P 50/P30/P25,480P60/P50/30/25	1080P60/P50/P30/P25,720P60/ P50/P30/P25
Network	1×RJ45:1×10M/100M(Support POE) 1. Video Output Format: Max 1080P60; 2. Image Compression: H.264/H.265 3. Protocol: ONVIF/RTSP /RTMP/TCP/UDP/SRT; 4. Audio Compression: AAC 5. Support multiple stream	1×10M/100M RJ45 (POE) Image Compression: H.265, H.264 Audio Compression: AAC, G.711 Video Output Format: 1080P60/P50/P30/P25; 720P60/P50/P30/P25; 360P60/P50/P30/P25
USB 3.0	1. Support UVC1.1 2. UVC Support: H.264/H.265/MJPEG: 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/P30/P25, 360P60/P50/P30/P25 YUY2:1080P30/P25, 720P30/P25, 480P30/P25, 360P30/P25 3. UAC Audio Format PCM	1×10M/100M RJ45 (POE) Image Compression: H.265, H.264 Audio Compression: AAC, G.711 1.Support UVC1.1. 2.UVC Video Format Support: H.264/H.265/MJPEG, 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/P30/P25, 360P60/P50/P30/P25;
3G-SDI	1080P60/P50/P30/P25, 720P60/P50/P30/P25	
Audio	1×LINE IN, 3.5mm	
Control Interface	1×RS-232 In 1×RS-232 Out/RS-485	
TF Card	Max support 256G	
PTZ		
Pan	-170° ~ +170°; 0.1° ~ 120°/s	
Tilt	-30° ~ +90°; 0.1° ~ 90°/s	
Preset Number	256	
General		
Power	DC12V; <15W	
Control Protocol	VISCA (support daisy chain) / PELCO-P / PELCO-D	
Operating Temperature	0°C ~ +40°C	
Storage Temperature	-20°C ~ +60°C	
Dimensions (L×W×H)	176mm × 137mm × 171mm	
Weight	≤1.2kg	
Ordering Information		
Product code		