



IKON 400

All-in-One Video Soundbar

Applications: Huddle room | Personal office



4K UHD
1080P



FOV
121°



BEAMFORMING
MICROPHONE



PLUG & PLAY



HI-FI SPEAKER



IKON 400

SPECIFICATION



Camera	
Video System	4K@30fps, 1080P@60fps,1080P@30fps, 720P@60fps, 720P@30fps
Sensor	1/2.5 inch, CMOS, 8.51M pixel
Lens	121° (DFOV) , 110° (HFOV) , 5x zoom, pan/tilt ±15°
PTZ	MPT + EPTZ
Digital Noise Reduction	2D&3D digital noise reduction
Video S/N	≥55dB
Backlight Compensation	Support

Audio	
Full frequency speaker	96 dB SPL in the case of 0.5 meter
Microphone array	Beamforming microphone, pick up distance up to 6 meters
External MIC	Support (Optional)

USB Features	
Connection type	USB 3.0, Downward compatible with USB2.0
Video Compression	H.264 / MJPEG /YUY2 /NV12
USB audio	32K sampling rate, support UAC2.0
USB video communication protocol	UVC 1.1~1.5
UVC PTZ control	Support

System Compatibility	
OS	Windows 7, Windows 8.1, Windows 10 or higher macOS® 10.10 2.4 GHz Intel® Core 2TM Duo processor or higher
Hardware platform	2 GB of memory or higher USB 2.0 interface (4K video output need USB 3.0 interface)

Input/output interface	
HD output	1*HDMI , version 2.0
Audio Interface	1*RJ45: D-MIC Input (Optional)
USB interface	1*USB3.0, Type C ; 1 * USB2.0, Type A ;
Wireless	Bluetooth
Power jack	DC 12V, 2A (MAX)

+91 452 4392222

sales@atnetindia.net

www.atnetindia.net

IKON 400

SPECIFICATION



Others

Control mode	2.4G remote controller
Installation mode	Support for desktop, wall, TV, and other installation options
Standard Cable	USB3.0 (2 meters)
Safety protection	Security lock jack

Generic Specification

Operating Temperature	0°C ~ 40°C
Storage Temperature	10°C ~ 60°C
Size	600mm x 140mm x 115mm
Net Weight	2.5 Kg

+91 452 4392222

✉ sales@atnetindia.net

www.atnetindia.net