



KLICK U2

USB PTZ CAMERA

Applications: Conference Room | Board Room | Classroom



1080P
FHD



72.5° (12X)
69° (10X)



12X/10X
OPTICAL ZOOM



16X
DIGITAL ZOOM



USB 3.0, HDMI,
RJ45 INTERFACES



A&T™

KLICK U2

SPECIFICATION



MODEL	Klick U2-12X	Klick U2-10X
Camera		
Image Sensor	1/2.8" CMOS, 2.14MP	
IRIS	4.14mm ~ 47.08mm	4.3mm ~ 43mm
Aperture value	F1.2 ~ F2.8	F1.6 ~ F3.0
HFOV	72.5° ~ 6.3°	69° ~ 8°
Optical zoom	12X	10X
Digital Zoom	16X	
Focusing System	Auto/Manual	
Shutter speed	1/50 ~ 1/10,000s	
Gain	Auto, Manual	
White Balance	Automatic, Manual, Automatic tracking, One Push, Static Color Temperature	
BLC	Support	
Wide Dynamic	Support	
Exposure	Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority	
SNR	≥50dB	
PTZ		
Pan	-170° ~ +170°; 0.1° ~ 100°/s	
Tilt	-30° ~ +90°; 0.1° ~ 70°/s	
Preset Number	64	
Interface		
HDMI	1080P60/P50/P30/P25, 720P60/P50	
Network	1×RJ-45:1×10M/100M 1. Video Output Format:Max 1080P60; 2. Image Compression:H.264/H.265 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 360P60/P50/P30/P25; 3. Protocol:ONVIF/RTSP/RTMP/TCP/UDP/RTMPS/GB28181; 4. Audio Compression:AAC 5. Support dual streams	
USB 3.0	1. Support UVC1.1 2. UVC Support: H.264/H.265/MJPEG, Video resolution:1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/P30/P25, 360P60/P50/P30/P25 YUY2:1080P30/P25, 720P30/P25, 480P30/P25, 360P30/P25 3. UAC Audio Format PCM	
Audio	1×LINE IN, 3.5mm	
Control Interface	1×RS-232 In, 1×RS-232 Out/RS-485	
General		
Power	DC12V; <8W	
Control Protocol	VISCA (support daisy chain) / PELCO-P / PELCO-D	
Operating Environment	Temperature: 0°C ~ +40°C, Relative Humidity: 10%RH ~ 90%RH	
Storage Environment	Temperature: -20°C ~ +60°C, Relative Humidity: 10%RH ~ 95%RH	
Dimensions (L×W×H)	176mm × 137mm × 171mm	
Weight	≤1.2kg	

+91 452 4392222

sales@atnetindia.net

www.atnetindia.net