



A&T[™]



ASTRA PRO LITE

Recording & Streaming System

ASTRA PRO LITE

SPECIFICATION



Parameters	
System structure	Embedded Linux system
Video input	1 x HDMI, 3 x RTSP / onvif Network Video Streaming
Video output	1 x HDMI
Maximum output resolution	1920*1080
Input resolution	3840×2160p@30、1920×1080p@60、1920×1080p@30 1600×1200P60、1680×1050p@60、1600×900P60、 1440×900P60、1280×1024p@60、1280×960p@60、 1280×800p@60、1280×720p@60、720×480p@60、 640×480p@60
Audio input	2 x 3.5mm line-in interface, 1*Phoenix MIC in port , 1 x HDMI IN
Audio output	1 x 3.5mm line-out interface , 1x HDMI OUT
Video encoding	H.264 , H.265
Audio encoding	AAC
Video output format	MP4, TS
Video encoding frame rate	25~60fps
Video bit rate	256kbps~20480Kbps adjustable
Audio bit rate	32~192Kbps adjustable
Data storage	Built-in>=2TB storage, support USB export, support FTP upload
Network	1 x RJ45 network ports
Serial port	1 x RS232 serial port
USB interface	1 x USB Type-A
Power parameters	DV 12V

+91 452 4392222

sales@atnetindia.net

www.atnetindia.net