

A performer with curly hair, wearing a black jacket over a striped crop top and black ripped jeans, is singing into a microphone on a stage. The stage is lit with blue and purple lights. A large purple rectangle is overlaid on the bottom left of the image, containing the text "SUPERIOR PRO AV TRACKING WITH NDI® HX3".

SUPERIOR PRO AV TRACKING WITH NDI® HX3

AVer **TR335N**

AI Auto Tracking PTZ Camera



NDI®

Equipped with NDI®|HX3 capability, AVer's new TR335N AI Auto Tracking PTZ Camera extends powerful and dependable Pro AV prowess to users across the spectrum of industries. The TR335N showcases proprietary functions — including Presenter Mode, Zone Mode, and Hybrid Mode tracking — driven by advanced AI processing. Seamlessly blending a 30X Optical Zoom lens, 4K 60 fps resolution, and the finesse of hybrid auto tracking and smooth PTZ operations, it's already the quintessential choice for broadcasting, streaming, or recording.



NDI® is a registered trademark of NewTek, Inc.
NDI®|HX is technology of NewTek, Inc.



NDI® HX3



4K Ultra HD
Resolution



30X Optical
Zoom



IP/HDMI/
USB/3G-SDI



5-Year
Warranty



Human
Detection AI



Presenter
Mode



Zone Mode



Hybrid Mode



Voice Tracking*

* Voice Tracking requires PTZ Link.

NDI® HX3 Levels Up Streaming

Elevate your streaming experience with the TR335N's cutting-edge NDI® HX3 technology! Revel in lossless, low-latency video streaming without complex configurations. This innovation is reshaping the landscape of contemporary video content sharing and production.




30X Optical Zoom Magnifies Details

Experience the exceptional power of the TR335N camera's astounding 30X optical zoom. This feature seamlessly operates even while the camera is panning and tilting, granting you the ability to accentuate content and quickly shift between shooting perspectives. Embrace the advantage of dynamic, crystal-clear video feeds through the TR335N's unparalleled PTZ performance.



HDMI / USB / IP. 4K 60 FPS.

Leverage the TR335N's 4K 60 fps streaming potential through HDMI, USB, and IP outputs. Free from intricate configurations and cable entanglements, you can effortlessly use multiple devices simultaneously to produce fluid video streams.



Presenter Mode

Get unparalleled tracking performance with Presenter Mode. This dynamic feature empowers presenters to venture beyond the stage to engage with their audience while the camera maintains seamless tracking.




Zone Mode

Zone Mode elevates your ability to capture content across multiple displays. Generate up to four dedicated Content Zones to consistently capture displayed information or items, prioritizing important presentation materials over the presenter's movements.



Hybrid Mode

Free your performers by enabling unrestricted movement with Hybrid Mode. Use preset areas for zone tracking, letting the camera seamlessly switch to a full view of each pre-defined location as performers move through the areas. If they move beyond these zones, the camera seamlessly adapts, switching to presenter mode to effortlessly and precisely track their movements.



Product Specifications

Camera		General		
Image Sensor	1/2.8" 4K Exmor CMOS	Power Requirement	AC 100 - 240V to DC 12V/5A	
Effective Picture Elements	8 Megapixels	Power Consumption	18W	
Output Resolutions	4K/60, 4K/59.94, 4K/50, 4K/30, 4K/29.97, 4K/25, 1080p/60, 1080p/59.94, 1080p/50, 1080p/30, 1080p/29.97, 1080p/25, 1080i/60, 1080i/59.94, 1080i/50, 720p/60, 720p/59.94, 720p/50	PoE	PoE+	
		Dimensions (W x H x D)	180.0 x 192.0 x 145.0 mm	
		Net Weight	2.0 (±0.1) kg	
Minimum Illumination	0.5 lux (IRE50, F1.6, 30fps)	Application	Indoor	
S/N Ratio	≥ 50 dB	Tally Lamp	Yes	
Gain	Auto, Manual	Security	Kensington Slot	
TV Line	1600 (Center)	Remote Control	Infrared	
Shutter Speed	1/1 to 1/32,000 sec	Operating Conditions	Temperature : 0 °C to +40 °C ; Humidity : 20% to 80%	
Exposure Control	Auto, Manual, Priority AE (Shutter, IRIS), BLC, WDR	Storage Conditions	Temperature : -20 °C to +60 °C ; Humidity: 20% to 95%	
White Balance	Auto, Manual	IP Streaming		
Optical Zoom	30X	Resolution	2160p 60fps	
Digital Zoom	12X	Network Video Compress Formats	H.264, H.265, MJPEG	
Total Zoom	360X	Network Audio Compress Formats	AAC-LC (48K), PCM (8K)	
Viewing Angles	DFOV : 69.2° (Wide) to 2.8° (Tele) HFOV : 62.3° (Wide) to 2.5° (Tele) VFOV : 37.3° (Wide) to 1.4° (Tele)	Maximum Frame Rate	2160p 60fps	
		Bit-Rate Control Modes	VBR, CBR (selectable)	
Focal Length	f = 4.5 mm (Wide) to 135 mm (Tele)	Range of Bit-Rate Setting	512 Kbps to 32 Mbps	
Aperture (Iris)	F = 1.8 (Wide) to 4.7 (Tele)	Network Interface	10 / 100 / 1000 Base-T	
Minimum Working Distance	0.1 m (Wide), 1.2 m (Tele)	Multi-Stream Capability	4 4K 60fps: RTSP, HDMI & USB 1080p 60fps: 3G-SDI	
Pan / Tilt Angles	Pan : ±170°, Tilt : +90° / -30°		Network Protocols	IPv4, TCP, UDP, ARP, ICMP, IGMP, HTTP, HTTPS, DHCP, RTP / RTCP, RTSP, RTMP, SRT, HLS, NDI, LLDP, VISCA over IP
Pan / Tilt Speed (Manual)	Pan : 0.1° to 100° / sec, Tilt : 0.1° to 100° / sec			
Preset Speed	Pan : 200° / sec, Tilt : 200° / sec			
Preset Positions	10 (IR), 256 (RS-232 / RS-422 / IP)			
Camera Control - Interface	RS-232 (DIN8), RS-422 (RJ45), IP, USB	NDI® HX3	Yes	
Camera Control - Protocols	VISCA (RS-232 / RS-422 / IP), PELCO-D & PELCO-P (RS-232 / RS-422), CGI (IP), USB, ONVIF			
Image Processing	Noise Reduction (2D / 3D), Flip, Mirror, WDR, BLC	USB		
Power Frequencies	50 Hz, 60 Hz	Connector	USB 3.1	
AI Auto Tracking Functions		Video Format	MJPEG, YUY2	
Tracking Modes	Presenter Mode, Zone Mode, Hybrid Mode	Audio Format	PCM	
Privacy Protection Mechanisms		Maximum Video Resolution	2160p	
Protection Mode	Sleep Mode	USB Video Class (UVC)	UVC 1.1	
AI Control Functions		USB Audio Class (UAC)	UAC 1.0	
Gesture Control	Yes	Web UI		
Audio		Live Video Preview	Yes	
Channel	2ch Stereo	Camera PTZ Control	Pan, Tilt, Zoom, Focus, Preset Control	
Codec	AAC-LC (48K), PCM (8K)	Camera/Image Adjustment	Exposure, White Balance, Picture	
Sample Rates	48 / 44.1 / 32 / 24 / 16 / 8 KHz	Network Configuration	DHCP, IP Address, Gateway, Subnet Mask, DNS	
Interface		Software Tools		
Video Outputs	3G-SDI, HDMI, IP, USB	IP Search and Configuration Tool	Support Windows® 7 or later	
Audio Outputs	3G-SDI, HDMI, IP, USB	PTZ Management	Support Windows® 7 or later	
Audio Inputs	Mic in, Line in	PTZ Control Panel	Supports iOS & iPadOS® 9 or later	
Warranty		PTZ Link	Supports Windows® 7 or later, macOS® 10.14 or later	
Camera	5 Years	OBS Plugin for PTZ Cameras	Supports Windows® 8 or later, macOS® High Sierra v10.13 or later	
Accessories	1 Year	CaptureShare	Supports Windows® 7 or later, macOS® 10.14 or later	
Package Contents	Camera, Remote Control, RS-232 In/Out Cable, Din 8 To D-Sub 9 Cable, Power Adapter, Power Cord, Cable Ties (x4), M2 x 4 mm Screws (x3), M3 x 6 mm Screws (x3), 1/4"-20L 6.5mm Screws (x2), Cable Fixing Plate, Ceiling Mount Brackets (x2), Drilling Paper, Quick Start Guide			
Optional Accessories	AVer CL01 PTZ Camera Controller, L-Type Wall Mount			

* Specifications may vary depending on location and are subject to change without notice.

Product Appearance

Front



Back



©2024 AVer Information Inc. All rights reserved.
All brand names and logos are trademarks of their respective companies.



Distributor/Dealer