



AirCast AC

Elevating presentation experiences - wirelessly

BYOD

Wireless Collaboration Device

AirCast AC

SPECIFICATION



| Technical Specifications | Receiver AC |
|--------------------------------|---|
| System | Linux |
| RAM | 256 MB |
| ROM | 512 MB |
| Interface | HDMI OUT 1.4*1, USB*3, RJ45*1, Audio*1, DC Power Jack*1 |
| Video Outputs | HDMI 1.4, comply with HDCP |
| Frame Rate | Up to 30 fps depending on environment (UHD) |
| Output Resolution | Max 3840*2160P(4K) |
| Input Resolution | Max 3840*2160P(4K) |
| Simultaneous Connections | 32 |
| Max. Display Windows | 4 |
| No.of Dongle Supported | 8 |
| Native Protocol | Miracast, Airplay |
| Wireless Transmission Band | 2.4 GHz & 5 GHz (Dual band Wi-Fi) |
| USB Touchback Support | Yes |
| Wireless Transmission Protocol | IEEE 802.11 a/g/n/ac |
| Authentication Protocol | WPA2-PSK(Pre-Share Key) |
| Wireless Speed | TX 300Mbps |
| Receiving Distance | No obstacle 50m |
| Support OS | Windows7/8/10, Mac OS, Chrome OS, Android, Linux, IOS 8.0 and above |
| Power Supply | DC5V, 2A |
| Power Consumption | 12W |
| Dimension(W*H*D) | 120mm X 120mm X 20mm |
| Operating Temperature | 0°~ 40°C |



+91 452 4392222

sales@atnetindia.net

www.atnetindia.net

CONNECTING YOU **ACROSS SPACE AND TIME**