



A&TTM



AirCast Pro2

Elevating presentation experiences - wirelessly

BYOD | BYOM

Wireless Collaboration Device

AirCast Pro2

SPECIFICATION



Technical Specifications	
HDMI output	1x HDMI 2.0, 1x HDMI 1.4
Main output Resolution	3840x2160@60Hz, 3840x2160@30Hz, 1920x1080@60Hz, 1280x720@60Hz, 1900x1200@60Hz, 1280x800@60Hz
Sub output Resolution	1920x1080@60Hz, 1280x720@60Hz 1900x1200@60Hz, 1280x800@60Hz
Format Compliance	HDMI1.4/HDMI2.0
Input video Capacity	1080P @ ≤30Hz Airplay, Miracast, Chromcast 1080P @ ≤30Hz "Wireless app" 4K @ ≤30Hz for HDMI dongle 4K @ ≤30Hz for USB-C dongle 4K @30Hz for HDMI wired input
HDCP	HDCP 1.4
HDMI Input	1x HDMI 19-pin female connector
Format Compliance	HDMI1.4
CEC	Support
Analog audio Output	Yes, 3.5mm jack
LAN port	RJ45 x2 1000Mbps
USB interface	USB-A 3.0 x3, USB-B 3.0x 1, Type-C(USB3.0) x1, USB 2.0 x3, Type-C(USB2.0) x1
USB Camera over wifi	≤1080P@30, MJPG
Audio Input	AirPlay/Miracast/Chromecast, Windows/MAC Apps, buttons, USB Mic
Audio output	jack, HDMI, jack + HDMI, USB Speaker
Control connectors	3 pin Phoenix terminal/ RS232 interface
Simultaneous screen and connection	5
Number of simultaneous connections	16(Max 2xAirplay or 2xMiracast or 2xChromecast, no limit with Apps and buttons)
Video Playback Frame Rate	20-60 FPS
Latency	80~120ms,
WIFI Data rate	Up to 1200Mbps
Wireless transmission protocol	WIFI IEEE 802.11 b/g/n/ac
Web security	HTTPS
Frequency band	2.4 GHz & 5 GHz
WIFI Antenna	MIMO 2x2 and MIMO 1x1
WIFI Encryption Control method	AES WPA PSK, WPA2 PSK Web GUI, Telnet, RS232
DC Power input	12V/3A
PoE	yes

+91 452 4392222

✉ sales@atnetindia.net

www.atnetindia.net