



AIR C1

Speakerphone

AIR C1

SPECIFICATION



AUDIO PARAMETERS

Microphone Pickup Distance	3m radius
Microphone Type	4-microphone array omni-directional
Frequency Response	100Hz ~8kHz
SNR	65dBA
Sensitivity	-26dBFS

AMPLIFICATION PARAMETERS

Channel Configuration	1
Power	1×5W Max
Impedance	4ohm
SPL(Maximum)	90dBSPL@1m, PN(Maximum power)
Distortion Level	≤1% @1W,1kHz
Signal-to-Noise Ratio	≥75dB
Duplex	Full Duplex
Frequency Response	100Hz~18kHz
Audio Technical Parameters	Auto Echo Cancellation, Noise Reduction, Automatic Gain Control, Dynamic Noise Suppression

I/O INTERFACES

USB	USB cable, USB Type C (with USB Type A adapter)
3.5mm Audio Jack	3.5mm audio jack for audio output
Buttons	Power, answer/hang-up, microphone, Bluetooth, multi- function
Indicator Lights	Supports (battery level / volume / microphone / incoming call and other prompts)

POWER SUPPLY

Battery	Built-in battery,1400mAh/3.7V
Battery Life	8 hours of talk time
Battery Charging	5V/1A;fully charged in 3 hours

BLUETOOTH PARAMETERS

Number of Bluetooth devices	1
Version	BT5.3+BLE
Operating frequency	2.4GHz
Operating distance	10m
USB Bluetooth dongle	Supports audio playback, high-definition audio input, compatible with Windows 7/8/8.1/10, MacOS 10.10 and above.

GENERAL INFORMATION

Operating Temperature	0°C~40°C
Product Dimension	120mm×120×36.5mm
Net Weight	255g