A&T™



PTC20N V.5

PTZ CAMERA

Applications: Board Room | Class room | Seminar Hall | Lecture Hall

1080P
FULL HD

20X
OPTICAL ZOOM

USB + HDMI + RJ45

BUILT IN STREAMING
SUPPORT



A&T™

PTC20N V.5

SPECIFICATION

A&T™
EXPERIENCE NEXT

Camera		
	Image Sensor	1/2.8" CMOS, 2.14 MP
	Iris	F1.6 ~ F3.5
	Focal Length	4.3mm ~ 130mm
	HFOV	60° ~ 2.9°
	Optical Zoom	20x
	Digital Zoom	16x
Other Camera Data		
	Focusing System	Auto, Manual, PTZ Trigger, One Push Trigger
	Shutter Speed	1/50 ~ 1/10,000s
	AGC	Auto, Manual
	BLC	Support
	White Balance	Auto, One Push, Manual, ATW, Static Color Temperature
	Wide Dynamic	Support
	Exposure	Auto, Manual, Shutter Priority, Iris Priority, Brightness Priority
	SNR	≥50dB
Interface		
	HDMI	1080P60/P50/P30/P25,720P60/P50/P30/P25,480P60/P50/30/25
	Network	1×RJ45:1×10M/100M 1. Video Output Format: Max 1080P60; 2. Image Compression: H.264/H.265 3. Protocol: ONVIF/RTSP/RTMP/RTMPS/RTP/TCP/UDP/SRT/HTTP; 4. Audio Compression: AAC 5. Support multiple stream
	USB 3.0	1. Support UVC1.1 2. UVC Support: H.264/H.265/MJPEG: 1080P60/P50/P30/P25, 720P60/P50/P30/P25, 480P60/P50/P30/P25, 360P60/P50/P30/P25 YUY2:1080P30/P25, 720P30/P25, 480P30/P25, 360P30/P25 3. UAC Audio Format PCM
	Audio	1×LINE IN, 3.5mm
	Control Interface	1×RS-232 In, 1×RS-232 Out/RS-485
	TF Card	Max support 256G
PTZ		
	Pan	-170° ~ +170°; 0.1° ~ 120°/s
	Tilt	-30° ~ +90°; 0.1° ~ 90°/s
	Preset Number	255
General		
	Accessories	USB Cable, HDMI Cable, RS232 Cable, IR Romote & Wall mount
	Camera Management Software	Yes
	Power	DC12V; <15W
	Control Protocol	VISCA (support daisy chain) / PELCO-P / PELCO-D
	Operating Temperature	0°C ~ +40°C
	Storage Temperature	-20°C ~ +60°C
	Dimensions (L×W×H)	176mm × 137mm × 171mm
	Weight	≤1.2kg

+91 452 4392222 sales@atnetindia.net www.atnetindia.net